UNITED 150



MATERIAL SAFETY DATA SHEET

320 37th Avenue, St. Charles, Illinois 60174 • 214 Dolomite Drive, Downsview, Ontario M3J 2N2 www.unitedlabsinc.com

To Reorder Call: 800-323-2594


1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

UNITED 150 CARBO-CLEAN

USE/DESCRIPTION Carburetor and Choke Cleaner

FOR MEDICAL AND TRANSPORTATION EMERGENCIES 24 Hour INFOTRAC (US and CANADA): 800-535-5053 **REVISION DATE** July 14, 2009



3 Ignites at normal temperature. 2 Ignites when moderately heated. 0 Will not burn.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS#	%Range	ACGIH (TLV-TWA)	OSHA (STEL-TWA)	LD50 (Species/Route)	LC50 (Species)
Acetone	67-64-1	70-80	500 ppm	1000 ppm	NE	NE
Toluene	108-88-3	15-20	20 ppm Ceiling: 300 ppm	NE	NE	NE
Carbon dioxide	124-38-9	3-5	5000 ppm	30000 ppm	NE	NE

3. HAZARDS IDENTIFICATION

Eyes: May cause eye irritation.

Skin: May be irritating to the skin.

Inhalation: Intentional misuse by concentrating and inhaling the product can be harmful or fatal. May be irritating to respiratory system. Prolonged inhalation may be harmful.

Ingestion: Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.

Chronic effects: Liver injury may occur. Kidney injury may occur. May cause central nervous system disorder (e.g. narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage.

4. FIRST AID MEASURES

Eyes: Immediately flush with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists. Skin: Wash off immediately with plenty of water. Remove and isolate contaminated clothing and shoes. If skin irritation persists, call a physician.

Inhalation: Move to fresh air. If symptoms persist, get medical attention. If breathing is difficult, give oxygen. Ingestion: Call physician immediately. Have victim rinse mouth thoroughly with water. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim indested the substance. Induce artificial respiration with other proper respiratory medical device.

5. FIRE FIGHTING MEASURES

Flash Point (TCC): -156°F/-104.4°C Propellant Explosive Limits: Lower (LEL): NE Upper (UEL): NE

Flame Projection (Aerosol): Extremely Flammable spray per 16 CFR 1500.3 and 1500.45.

Hazardous Products of Combustion: When strongly heated, as in a fire, this product may produce irritating, corrosive and/or toxic gases.

Fire and Explosion Hazards: Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing Media: Water, Alcohol foam, Dry chemical, Carbon dioxide.

Fire Fighting Instructions: Wear self-contained breathing apparatus w/full protective clothing in chemical fires. Do not breathe fumes. Cool fire exposed containers to prevent pressure build up. Cool containers with flooding quantities of water until well after fire is out.

6. ACCIDENTAL RELEASE MEASURES

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly. After removal flush contaminated area thoroughly with water.

Large Spills: Remove sources of ignition and ventilate area. Contain liquid. Soak up with an inert absorbent and place in designated disposal container. Prevent run-off to sewer.

7. HANDLING AND STORAGE

Do not expose to temperatures exceeding 120°F/49°C. Store in a cool well-ventilated area, away from sources of ignition. Do not pierce or burn, even after use. Use only in area provided with appropriate exhaust ventilation. Keep out of reach of children. Wash hands before eating or smoking after using aerosol. NFPA Code 30B Rating: Level 2 Aerosol.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Chemical googles are recommended.

Skin: Chemical resistant gloves are recommended. Wear appropriate chemical resistant clothing.

Respiratory: Not normally required. If vapor concentration exceeds TLV, use a NIOSH or MSHA mechanical filter/organic vapor cartridge or an air-supplied approved respirator.

Engineering Controls: Provide adequate ventilation to keep vapor concentration below TLV and prevent accumulation of excessive vapors.

9. PHYSICAL AND CHEMICAL PROPERTIES

 Boiling Point:
 152.6°F/67.2°C estimated
 Specific Gravity:
 0.8056 estimated
 Vapor Pressure:
 ND
 Melting Point:
 ND

 Vapor Density:
 ND
 Evaporation Rate:
 ND
 Solubility in Water:
 Partially
 pH:
 N/A

 Appearance and Odor:
 Clear, colorless aerosol spray with solvent scent.
 Solubility in Water:
 Partially
 PH:
 N/A

10. STABILITY AND REACTIVITY

Hazardous Polymerization: NA Hazardous Decomposition: When strongly heated, as in a fire, this product may produce irritants, toxic gas, and may include oxides of Sulphur. Chemical Stability: Risk of ignition.

Incompatibility: Oxidizing agents such as bleach.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity (NTP/IARC/OSHA): None

California Proposition 65: Does this product contain chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm? Yes (Toluene CAS # 108-88-3)

12. ECOLOGICAL INFORMATION

ND

13. DISPOSAL CONSIDERATIONS

Consult your local, state, and federal regulations for proper disposal guidelines. Do not puncture, incinerate or crush containers. Dispose of this material and its container at hazardous or special waste collection point. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001 & D018 Waste Benzene. Disposal regulations may be different for each state and/or locality.

14. TRANSPORT INFORMATION

DOT: Available upon request **TDG:** Available upon request **UN:** Availabale upon request

15. REGULATORY INFORMATION

VOC (Volatile Organic Compounds): ND TSCA (Toxic Substances Control Act): Listed SARA Title III Section 302 EHS: No SARA Title III Section 311/312: Yes SARA Title III Section 313 Toxic Chemicals: Toluene CAS#108-88-3, WHMIS Classification:

This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations/ WHMIS) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

Read and follow all label directions and precautions before using this product. These products are intended for industrial and institutional use only. NOT FOR HOUSEHOLD USE OR RESALE. KEEP OUT OF REACH OF CHILDREN.

UNITED 150 CARBO-CLEAN

PREPARED BY: Sandy Kopacz