

UNITED

LABORATORIES

With **FORMULA TLD15** on the job, batteries work better and last longer.

Provides a one-step solution to battery terminal corrosion removal and acid neutralization. Delivers a powerful, heavy-duty foam that clings to battery surfaces, provides extended contact time and neutralizes acid quickly. Helps eliminate power leaks and aids in restoring full starting power.

FORMULA TLD15 features a low-odor, non-flammable, water-soluble formula. Contains a unique color indicator; product sprays out yellow and changes to red to indicate the presence of acid.

When battery cleaning is finished, it leaves behind a residual film that provides short-term resistance to corrosion.

Use **FORMULA TLD15** on:

- Fleet Cars
- Marine Equipment
- Agricultural Equipment
- Construction Equipment
- Industrial Battery Back-up Systems
- Buses
- Trucks
- Forklifts
- Golf Carts

DIRECTIONS:

SHAKE WELL BEFORE USING. Be sure cell covers are tightly sealed. Spray on cables, clamps, terminals, brackets, housings and entire battery surface. Product will spray out light yellow in color and turn red in the presence of acid. Allow foam to work for several minutes and then flush with water. Follow with a second application. If solution still turns red, acid neutralization process is not complete. Allow to set then repeat. For heavy deposits, agitation with a wire brush may be needed. If sprayed foam remains yellow, all acid has been neutralized. Allow product to dry and form residual protective film.

FORMULA TLD15

Battery Protector and Cleaner

UNITED 167

KEEP OUT OF REACH OF CHILDREN.

CAUTION:

CONTENTS UNDER PRESSURE.
SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS.

PRECAUCION AL USARIO: Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

NET WEIGHT: 18 OZ. (510 GRAMS)

Sold By:

UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

CAUTION:

Contains Liquefied Petroleum Gas (CAS# 68476-86-8) and Ethylene Glycol Monobutyl Ether (CAS# 111-76-2).

Do not puncture or incinerate container. Do not expose to heat, sparks or open flame. Do not store at temperatures above 120° F.

FIRST AID MEASURES:

EYES: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN: Wash with soap and water. If irritation persists seek medical attention.

INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

INGESTION: DO NOT induce vomiting. Seek medical attention immediately.

An MSDS for this product has been provided. Please read it carefully and follow all instructions when using or handling this product.

HMIS III® CODE:

0=MINIMAL	HEALTH	1
1=SLIGHT	FLAMMABILITY	0
2=MODERATE	PHYSICAL HAZARD	0
3=SERIOUS	PERSONAL PROTECTION	A
4=SEVERE		

PERSONAL PROTECTION INDEX: Glasses

Manufactured & Printed in U.S.A.

309