



UNITED

LABORATORIES

United 315 Idle System Corrosion Inhibitor is a non-toxic, environmentally inoffensive corrosion inhibitor for use in any static water system.

- Leaves a protective coating
- Prevents corrosion
- Prolongs equipment life
- Non-toxic—no chromate

MANY USES:

- Hot/Chilled water systems
- Sprinkler systems
- Cooling tower storage
- Fire departments

DIRECTIONS FOR USE:

Idle Hot or Chilled Water Loops: Drain and thoroughly flush old water. Refill system with fresh water adding one gallon of **United 315** for each 500 gallons (1 litre for each 500 litres) of system capacity. Circulate briefly to mix uniformly.

Sprinkler Systems: Meter one gallon of **United 315** into the system for every 500 gallons (1 litre for every 500 litres) of system capacity. **United 315** does not accelerate combustion under any conditions.

Cooling Towers: Cooling towers in idle storage may be protected against corrosion by circulating one gallon of **United 315** for every 500 gallons (1 litre for every 500 litres) of system capacity for 24 hours before draining the system. **DO NOT** allow **United 315** to concentrate, as a silicate buildup may result.

Fire Departments: **United 315** may be used in tanker trucks and other equipment where fire-fighting water is stored. Add **United 315** at one gallon per 500 gallons (1 litre per 500 litres) of tank capacity. Circulate if possible to assure uniform mixing.

United 315

Idle System Corrosion Inhibitor

KEEP OUT OF REACH OF CHILDREN.

CAUTION

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

PRECAUCION AL USUARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

CAUTION:

Harmful if swallowed.

EMERGENCY AND FIRST AID PROCEDURES:

SKIN: Wash thoroughly with soap and water. If irritation persists, call a physician or poison control center.

EYES: Flush with plenty of tepid water for at least 15 minutes while holding eyelids open. If irritation persists call a physician or poison control center.

IF INHALED: Clear patient's airway immediately. Apply CPR if needed. If irritation persists, call a physician or poison control center immediately.

IF SWALLOWED: Drink several glasses of water to dilute. If stomach upset persists, call a physician or poison control center.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Gloves and Goggles	HEALTH	1
	FLAMMABILITY	0
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	n&p