

UNITED

L A B O R A T O R I E S

United 323

GENERAL INFORMATION:

United 323 is formulated for corrosion and scale control in closed loop heating and cooling systems.

- Molybdate protects ferrous metal components.
- Aromatic azoles protect non ferrous "yellow" metal components.
- Sequestrants prevent scale build-up.
- Contains no phosphate or chromate.

DIRECTIONS FOR USE:

For initial treatment, add 1 gallon of **United 323** for each 100 gallons (1 litre for each 100 litres) of water in the chilled water recirculating system. This is most easily done with a pot feeder or a force-and-suction pump. If using a pot feeder larger than the required dose, top up the chamber with water to prevent air entering the system.

Twenty-four to forty-eight hours after initial treatment, test a sample of water for molybdate. Your United Laboratories representative can arrange this test. A molybdate level in the range 30 to 50 ppm is desired. Re-check product level every 90 days, or more frequently if water loss and replacement is known to occur.

Closed Loop Chiller System Treatment

KEEP OUT OF REACH OF CHILDREN.

CAUTION

HARMFUL OR FATAL IF SWALLOWED.

**SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS.**

PRECAUCION AL USUARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

**Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.**

**320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com**

CAUTION:

Contains Sodium Nitrite (CAS # 7632-00-0), Potassium Hydroxide (CAS # 1310-58-3) and Sodium Molybdate (CAS # 10102-40-6). Can cause burns to skin and eyes. Highly toxic; do not take internally. Harmful or fatal if swallowed.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Immediately flush with plenty of water for at least 15 minutes while holding eyelids open. Call a physician immediately.

SKIN: Wash with soap and water. If irritation persists call a physician.

INHALATION: Remove to fresh air. Apply CPR as necessary and call a physician immediately.

IF SWALLOWED: If conscious, give large amounts of water then induce vomiting by touching back of throat with finger. Keep head below hips to prevent aspiration of liquid into lungs. Call a physician immediately.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Gloves and Goggles	HEALTH	2
	FLAMMABILITY	0
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	n&p