

UNITED

LABORATORIES

United 324

- Clarifies swimming pools clouded by high iron levels
- Prevents rust stains in laundries
- Prevents rust stains in porcelain fixtures
- For controlling red rust in potable water

DIRECTIONS:

Normally, one gallon of this water conditioner will treat 50,000 gallons of water. Severe conditions may require higher dosages. Federal drinking water standards allow use of up to 2 1/2 gallons per 50,000 gallons of potable water. This product is best applied by a water meter controlled injection system, but may be slugfed into storage tanks.

HMIS® III CODE: 0=MINIMAL 1=SLIGHT	HE
2=MODERATE	FL
3=SERIOUS 4=SEVERE PERSONAL	PH
PROTECTION INDEX: Glasses and Gloves	PE

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	В

Water Conditioner

KEEP OUT OF REACH OF CHILDREN. CAUTION

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

CAUTION:

Contains Tetrasodium Pyrophosphate (CAS# 7722-88-5). Avoid contact with eyes and skin. This product is non-toxic in use dilutions. The concentrate should be stored in a safe place, out of reach of children.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with plenty of water for at least 15 minutes. Hold eyelids open during this flushing. Call a physician immediately.

SKIN: Wash with soap and water. If irritation persists, get medical attention.

INHALATION: Remove victim to fresh air. If not breathing, give artificial respiration. Call a physician.

IF SWALLOWED: If conscious, drink a quart of water. DO NOT induce vomiting. Call a physician immediately.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.