

**Makes Ceiling Tiles Look Like New**

- Will not cause warping
- Avoids costly tile replacement or complete re-painting



Designed to restore the appearance of ceiling tiles that are stained or discolored. When used as directed, **UP WHITE** will extend the practical life of ceilings by keeping them looking good.

Seals and covers water stains, smoke, graffiti, paint, ballpoint ink, permanent marker and rusting nail heads. Permanently bonds to the surface without compromising sound absorption properties and fire retardant value.

**DIRECTIONS:**

**Read Warnings and Directions CAREFULLY before using.** When spraying suspended ceiling tiles, cover everything under area with cloth or newspaper. Whenever possible, remove tiles and place on flat surface for spraying. Test **UP WHITE** in a small area first to determine color match.

Apply product at temperatures above 65°F (18°C). One can covers 12-15 (2' x 4') tiles or 120 square feet.

1. Clean surface thoroughly to remove grease, dust and other foreign matter.
2. Shake can vigorously before and during use.
3. Hold can about 12 inches away and spray one light coat over surface. Allow to dry, then follow with a second light coat.
4. After use, turn can upside down and spray to clear nozzle. If nozzle becomes clogged, remove and hold under warm, running water.

For food plant and other industrial use, avoid contamination of food in the application and storage of the product. Do not use on food contact surfaces.

**WARNING: FLAMMABLE. VAPORS HARMFUL.**

MEETS CALIFORNIA VOC REACTIVITY LIMIT OF 1.20 FOR FLAT PAINT PRODUCTS.

**CONTAINS (CAS#):** Propane/n-Butane (68476-86-8), Isoparaffinic Hydrocarbon (64742-47-8), Acetone (67-64-1), Titanium Dioxide (13463-67-7), Ethyl Alcohol (64-17-5), Heptane (142-82-5).

**HMIS® III CODE:**

0=MINIMAL	HEALTH/SANTÉ	2
1=SLIGHT	FLAMMABILITY/INFLAMMABLE	3
2=MODERATE	PHYSICAL HAZARD/ RISQUE PHYSIQUE	1
3=SERIOUS	PERSONAL PROTECTION/ PROTECTION PERSONNELLE	B
4=SEVERE		

**PERSONAL PROTECTION INDEX:** Goggles and Gloves

Manufactured and Printed in U.S.A.

809

# UNITED

LABORATORIES

**UP WHITE**  
**ACOUSTICAL CEILING**  
**TILE WHITENER**

**UNITED 190**




**KEEP OUT OF REACH OF CHILDREN.**  
**DANGER**  
**FLAMMABLE LIQUID AND VAPOR.**  
**VAPORS MAY CAUSE FLASH FIRE.**  
**CONTENTS UNDER PRESSURE.**  
**SEE ADDITIONAL PRECAUTIONS ON BACK PANEL.**

*PRECAUCION AL USARIO: Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.*

**NET WEIGHT: 12 OZ. (341 grams)**

**UNITED LABORATORIES, INC.**  
320 37th Avenue • St. Charles, IL 60174  
1-800-323-2594 • www.unitedlabsinc.com

**UNITED 190 UP WHITE**  
**Acoustical Ceiling Tile Whitener**  
UNITED LABORATORIES OF CANADA, INC.  
214 DOLOMITE DRIVE DOWNSVIEW, ONTARIO M3J 2N2  
An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product.  
Un MSDS ce produit absenter disponible un site un Internet www.unitedlabsinc.com, fournir 24 heures accès. Ai lu s'il vous plaît le MSDS et soigneusement ensuis de toutes instructions quand utiliser ou manipuler ce produit.

**DANGER!** This product is a flammable aerosol. Contents under pressure. It may explode if heated. Contents cause irritation to the eyes and skin. Harmful if inhaled. Harmful if swallowed.  
**PRECAUTIONS:** Avoid contact with eyes and skin. Wear safety glasses and gloves when handling or using this product. Wash thoroughly after handling. Do not ingest. Keep away from heat, open flames or other sources of ignition. Provide adequate ventilation. Do not puncture or incinerate this container, even when empty. Do not store at temperatures over 49°C (120°F).  
**FIRST AID MEASURES: EYES:** Flush with plenty of cool water for at least 15 minutes while holding eyelids open. Call a physician or poison control center immediately. **SKIN:** Wash with soap and water. If irritation persists, call a physician. **INHALATION:** Remove to fresh air. Call a physician or poison control center immediately. If not breathing, give artificial respiration. **INGESTION:** DO NOT induce vomiting. Call a physician or poison control center immediately.  
**LE DANGER!** Ce produit est un aérosol inflammable. Les contenus sous contraignent. Ça pourrait exploser si ai chauffé. Les contenus causent l'énerverment l'œil et de la peau. Si nuisible ai inhalé. Si nuisible ai avalé.  
**PRÉCAUTIONS:** Échappe contacte avec un œil et de la peau. Porte la sécurité lunettes et gante quand manipuler ou engager des poursuite ce produit. Après débarbouille entièrement manipuler. N'ingurgitez pas. N'approche pas de d'ouvrir chaleur ou d'autres provenances d'allumage et flambe. Fournis ventilation adéquate. Ne ponctionne pas ou incinère ce récipient et égalise quand vidange. N'engrange pas dessus 49°C de températures (120°F).  
**PROCEDÉS DE PREMIERS SOINS: YEUX:** Avec encastre Calmer beaucoup d'arrose au bas mot 15 procès-verbal pendant que des paupières tenant ouvre. Appelle un médecin ou empoisonne contrôlé axe immédiatement. **PEAU:** Se débarbouille avec du savon et l'eau. Si l'énerverment s'obstine appelle un médecin. **L'INHALATION:** Enlève à un air fraîche. Appelle un médecin ou empoisonne contrôlé axe immédiatement. Si pas respirer donne respiration artificielle. **L'INGESTION:** Ne provoque pas vomir. Appelle un médecin ou empoisonne contrôlé immédiatement.