



UNITED

LABORATORIES

SHAKE WELL BEFORE USING.

NOMIX is a heavy-duty polyurea polymer filler for repairing cracks, gouges, holes and surface delamination in concrete. Ideal for use in warehouses, garages, shops or anywhere cracks in concrete floors are a problem.

NOMIX is formulated to minimize downtime:

- Convenient dual cartridge and static mixer eliminates mixing.
- Works at temperatures as low as -20° Fahrenheit.
- Fast setting. **NOMIX** will withstand heavy traffic within 30 minutes.
- Low odor.
- Becomes hard and rubber-like when cured. Won't become brittle with aging.

DIRECTIONS FOR USE:

Surface should be free of dirt, debris, frost or moisture. Surface preparation is important to assure proper adhesion.

Using the A541 **NOMIX** Dual Feed Dispenser with Static Mixer, fill the cracks being repaired. Cured filler can be shaved to level with a razor. For wider applications, fill crack as flush as possible to the surface. Using a belt-sander with 40, 60, or 80 grit paper, level the **NOMIX** with the floor.

United 541 NOMIX is a two component material that needs to be applied with a special two part dispensing gun—the A541 **NOMIX** Dual Feed Dispenser. It mixes the proper amount of the two components during application.

APPLICATIONS BELOW FREEZING: When applying at temperatures below 32°F (0°C) pre-warm cartridges to 90°F (33°C). This can be done using heated water or a heated box.

United 541

NOMIX Concrete Repair

KEEP OUT OF REACH OF CHILDREN.

WARNING

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

WARNING:

Contains di-(methylthio) Toluenediamine (CAS # 106264-79-3), Polyethylene polypropylene glycol glycerol ether (CAS # 9082-00-2) and modified Isocyanate (CAS # 101-68-8), and Aliphatic Polyisocyanate (CAS # 28182-81-2).

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mist. Use with forced ventilation. Moisture contamination may cause dangerous pressure buildup. Keep container closed.

FOR INDUSTRIAL USE ONLY.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Immediately flush with plenty of cool water for at least 15 minutes, while holding eyelids open. Get prompt medical attention.

SKIN: Wash with soap and water. If irritation persists, call a physician or poison control center.

INHALATION: Remove to fresh air. Apply CPR if needed. Call a physician or poison control center.

IF INGESTED: DO NOT induce vomiting. Immediately drink water to dilute. Get medical attention immediately if symptoms develop. Never give anything by mouth to an unconscious person.

NOTE TO PHYSICIAN:

Individuals sensitized to isocyanate should not be exposed to this product.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Gloves and Goggles	HEALTH	2
	FLAMMABILITY	1
	PHYSICAL HAZARD	1
	PERSONAL PROTECTION	n&p