

UNITED

LABORATORIES

SOLAR GOLD

630

Responsible Innovation™ - **SOLAR GOLD Grease Trap Maintainer** harnesses the power of nature's resources to provide a bio-based blend that is uniquely suited for breaking through fats, oils and grease.

- NPE-Free.
- Non-caustic.
- Non-corrosive.
- Contains no petroleum distillates.
- Contains no chlorinated hydrocarbons.
- Deodorizes with a fresh citrus scent.

DIRECTIONS

Use a sufficient quantity of **SOLAR GOLD Grease Trap Maintainer** to provide approximately a 1" (2.5 cm) layer of the solvent on the surface of the grease trap. One quart (946 mL) of product will cover 60 square inches (387 square centimeters) of surface with the recommended layer of 1". A grease trap one foot square (.1 square m) will require a little over two quarts (1.9 L) for the initial maintenance dosage. Thereafter add one pint (473 mL) per week for normal loading.

Traps which carry heavy loads of fats, oils and greases, will require larger or more frequent maintenance dosages. **SOLAR GOLD** can be poured into the drain nearest the grease trap, or the grease trap cover can be removed, and **SOLAR GOLD** can be added directly to the trap. If the trap is heavily loaded with grease it is suggested a manual cleaning of the trap be done, before the initial dosage of **SOLAR GOLD** is added. Under normal conditions, the regular use of **SOLAR GOLD** should reduce the need for manual cleaning of the trap.

When using a metering pump with this product, you must use Viton® tubing.

Manufactured and Printed in U.S.A.

212

Grease Trap Maintainer

KEEP OUT OF REACH OF CHILDREN.

CAUTION

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

PRECAUCION AL USUARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

CAUTION

Contains d-1,8 (9)-p-Menthadiene (CAS #5989-27-5). **SOLAR GOLD Grease Trap Maintainer** is combustible and should be stored in a cool place away from exposure to extreme heat and open flames. It may ignite and burn on heating above 110°F (43°C). Product may catch fire in use.

Harmful if swallowed. Avoid eye and skin contact.

EMERGENCY AND FIRST AID PROCEDURES

EYES: Flush with plenty of tepid water for at least 15 minutes while holding eyelids open. Call a physician or poison control center immediately.

SKIN: Wash with soap and water. If irritation persists, call a physician or poison control center.

INHALATION: Remove to fresh air. Apply CPR if needed. Call a physician or poison control center immediately.

INGESTION: DO NOT induce vomiting. Call a physician or poison control center immediately.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Gloves and Goggles	HEALTH	1
	FLAMMABILITY	2
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	B