



UNITED

LABORATORIES

United 844 Devour Power for Grease Trap Maintenance is a specially formulated blend of microbes selected for their ability to bio-degrade high volumes of grease including long-chain fatty acids other products cannot break down. More importantly, **Devour Power for Grease Trap Maintenance** provides the means to bio-degrade the fats, oils and greases (FOG) that are trapped in grease traps without using surfactants. The bio-degradation of the grease devours it and prevents it from simply being mobilized further down the drain.

The unique formulation of **United 844 Devour Power for Grease Trap Maintenance**:

- Contains patented gram-positive bacterial strains to bio-degrade long-chain fatty acids.
- Includes promicrobials which are capable of fast degradation of FOG.
- Has a pH range from 4.5 to 9.8.
- Works with an effective temperature range of 45°– 120°F.
- Maintains optimal FOG degradation through three-fold action.
- Has passed the EPA Methods 1664 and 1664A, proving the grease is not mobilized and allowed to pass through the grease trap.
- Reduces odors that lead to concern from sanitation inspectors.
- When combined with proper kitchen procedures, reduces excessive grease trap pumping by increasing FOG degradation.

DIRECTIONS FOR USE:

Dosage rates for grease traps:

For best results treatment should be done after the kitchen has shut down for the day. If kitchen is open 16 hours or more per day, call your United sales representative for additional dosage rates and recommendations.

United 844

Devour Power for Grease Trap Maintenance

KEEP OUT OF REACH OF CHILDREN.

CAUTION

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

DIRECTIONS FOR USE: (continued)

Recommendation: To assure that your system is maintained as effectively and efficiently as possible utilize the programmable United A855 or A877 Peristaltic Metering Pumps to automatically feed **Devour Power for Grease Trap Maintenance** into your drains as needed around the clock.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with plenty of water for at least 15 minutes and call a physician or poison control center.

SKIN: Wash with soap and water. If irritation persists, call a physician or poison control center.

INHALATION: Not applicable.

INGESTION: Rinse mouth and throat. Give two glasses of water to dilute product. DO NOT induce vomiting. Call a physician or poison control center.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Glasses	HEALTH	1
	FLAMMABILITY	0
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	A