

UNITED

LABORATORIES

GENERAL INFORMATION:

- Ideal cement for the construction and repair of all flashing, parapet walls, coping and chimneys.
- Suited for sealing cracks, holes and tears in built-up roofs (asphalt and coal tar) and modified bitumen single plys.
- High performance rubberized elastomeric cement.
- Tensile strength of 600 psi minimum.
- Remains flexible and watertight.
- Elongation – 400%.
- May be used in standing water.
- Fill joints up to 2" wide without sag.
- Covers 12-25 square feet per gallon.

United 16 SPECIAL OPS is a unique professional grade elastomeric flashing and repair product that cures to a long lasting rubber membrane. **United 16** remains flexible through extreme temperature ranges. **United 16** is ideally suited for sealing cracks, holes and tears in built-up roofs (asphalt and coal tar), and modified bitumen single plys. **United 16** is an excellent cement for sealing laps in sheet metal roofs. It may also be used as a patch and repair for EPDM rubber sheets.

United 16 is not recommended for use as an adhesive. DO NOT USE FOR ADHERING SHINGLE TABS OR UNDER ROOFING FELTS AND MEMBRANES. If unsure about compatability, test in an inconspicuous area first.

DIRECTIONS FOR USE:

Prior to application, the surface needs to be free from oil, grease and other foreign material. The surface must be firm and free from loose material and dust. Any loose nails must be driven in and capped with **United 16. SPECIAL OPS** is designed to be applied with a trowel or caulk gun. Spread product evenly and feather all edges of the repair. Apply a minimum wet thickness of 1/8" to 1/4" per single coat. (Allow 24 hours of drying time before applying a top coat, if desired). Only apply **United 16** when temperatures will remain at 40°F or higher for 24-48 hours to allow proper curing. Do not thin.

United 16

SPECIAL OPS

Wet/Dry Roof Patch And Flashing Cement

KEEP OUT OF REACH OF CHILDREN.
WARNING: FLAMMABLE
**SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS.**

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Sold By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

CAUTION:

Use out of doors in well ventilated areas only. Keep away from heat, sparks, and open flame. Avoid prolonged or repeated contact with skin or breathing of vapors. Do not take internally.

United 16 is manufactured from a pure neoprene base and contains no asphalt or other bituminous materials.

Store material in temperature of 60°-80°F, out of sunlight.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Immediately flush with plenty of water for at least 15 minutes while holding eyelids open. Call a physician or poison center immediately.

SKIN: Wash skin with waterless hand cleaner followed by soap and water. If redness appears treat it as a sunburn, if redness persists or rash appears call a physician or poison center immediately.

INHALATION: Remove to fresh air, upwind from fume source. If irritation persists, call a physician or poison center immediately.

INGESTION: DO NOT induce vomiting. Prevent aspiration into lungs. Even a small amount into lungs may result in aspiration pneumonitis. Call a physician or poison center immediately.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

| | | |
|---|---------------------|---|
| HMIS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Glasses and Gloves | HEALTH | 2 |
| | FLAMMABILITY | 2 |
| | PHYSICAL HAZARD | 0 |
| | PERSONAL PROTECTION | B |