

UNITED

LABORATORIES

United 572 SHIELD is a water-based acrylic sealer for industrial use where durability and chemical resistance is required. **United 572 SHIELD** provides safe, easy and economical application and cures quickly for minimum downtime. **United 572 SHIELD** has no harmful odors, dries to a clear, colorless film.

United 572 SHIELD may be used on concrete, brick, slate, exposed aggregate, quarry tile, unglazed ceramic tile, Mexican tile and masonry walls and floors.

United 572 SHIELD...

- Outstanding Interior and Exterior Performance
- Water-based
- Water Resistant
- Non-Yellowing
- Long Lasting
- Easy to Apply
- Brightens Stone Work
- Excellent Soil Resistance (per ASTM D3206)
- Contains 25% Solids
- Low Sensitivity to Amine-containing Strippers
- VOC Compliant in All States

Coverage Rates by concrete type:

Rough/Course: 500-800 square feet per gallon
Medium Porosity: 700-1000 square feet per gallon
Smooth: 1000-1500 square feet per gallon
Previously Coated: 1000-1500 square feet per gallon

DIRECTIONS FOR USE:

Remove all grease, oil and other foreign material by scrubbing with a heavy duty cleaner degreaser such as United 366 GOOD NEWS Heavy-Duty Cleaner Degreaser and a wire brush. Rinse thoroughly with clean water and allow to dry. Put down a test patch if there is any question of adhesion. For best results, apply with an A093 Lamb's Wool Applicator or a low pressure sprayer (recommended 40 psi.) such as the A042 Compression Sprayer. Avoid the use of a mop on rough substrates.

Depending on conditions, allow 20 minutes to 40 minutes dry time. Three coats are recommended to ensure protection and higher gloss. Allow two hours between coats when humidity is below 70%; Allow four hours between coats when humidity exceeds 70%. The final coat should dry 6 to 8 hours before subjecting to heavy traffic. For use as a membrane curing compound, apply as noted above with a coverage rate of 200 square feet per gallon.

NOTE: Remove any exposed food or food products from area where coating is being applied.

United 572

SHIELD

Water-Based Acrylic Concrete Sealer

KEEP OUT OF REACH OF CHILDREN.
CAUTION
**SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS.**

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

DIRECTIONS FOR USE: (continued)

DO NOT APPLY TO NEW CONCRETE LESS THAN 30 DAYS OLD. DO NOT POUR UNUSED MATERIAL BACK INTO ORIGINAL CONTAINER (It will damage the product.) AVOID EXPOSURE TO STANDING WATER FOR 25 HOURS.

CAUTION:

Keep out of eyes as it may cause irritation. Prolonged and repeated exposure may cause skin irritation, defatting or dermatitis. Excessive inhalation of vapors can cause nasal or respiratory irritation. Do not ingest.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with plenty of cool water for at least 15 minutes while holding eyelids open. Call a physician or poison center immediately.

SKIN: Remove contaminated clothing. Wash with soap and water. If irritation persists, call a physician or poison center.

INHALATION: Remove patient to fresh air. Apply CPR if needed. If irritation persists, call a physician or poison center.

INGESTION: If conscious, induce vomiting by giving either syrup of ipecac followed by 2 glasses of water or by sticking finger down throat. Call a physician or poison center immediately. Do not give anything by mouth if the person is drowsy, unconscious or has no gag reflex.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, for 24-hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Glasses and Gloves	HEALTH	1
	FLAMMABILITY	0
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	B