

# UNITED

LABORATORIES

- Penetrates and Protects Your Floor
- All Acrylic Formula Provides a Clear Non-yellowing Film
- Versatile—Seals All Types of Floors
- Detergent Resistant
- Non-Flammable
- Prevents Dusting of Concrete

#### SPECIFICATIONS:

Nonvolatile ( $\pm$ .4%) ASTM D-2834-72: .....	16.0%
pH ( $\pm$ 0.3): .....	8.3
Drying Time, Initial Coat (75°F, 50% R.H.): .....	25 Min.
Density (lb/gal): .....	8.55
Storage Stability: .....	1 yr. Min.
Slip Resistance (ASTM D-2047-82): .....	0.525 Min.
Water Resistance (ASTM D-3207-82): .....	Excellent
Removability (ASTM D-1792-82): .....	Very Good
Sediment (ASTM D-1290): .....	<0.10%
Recoat Time (75°F, 50% r.h.): .....	30 Min.
Freeze/Thaw Stability: .....	Keep from Freezing
Refractive Index (20°C): .....	1.369
Coverage: .....	1500-2000 sq. ft./gal.

**FOR USE ON:** Vinyl, asbestos, rubber and asphalt tile, linoleum, terrazzo cement, masonry and brick.

**DESCRIPTION:** This formula represents the latest technology advancement in floor sealers. Its all acrylic polymer blend penetrates and seals virtually any floor including composition tile, terrazzo and concrete. **United 69** provides an excellent base for all floor finishes. It has exceptional detergent resistance for high speed or scrub and recoat floor care programs. Will not oxidize or darken. Brings out the original beauty of old surface. Keeps floors from becoming unattractive due to heavy traffic, spilled food, shuffling feet, sweeping, mopping and the like. Prevents the floor from becoming dull, spotted and hard to clean.

#### DIRECTIONS:

After the floor has been thoroughly washed, rinsed and dried, apply **United 69** with a short cotton mop or lambswool applicator. If the floor is porous, a second coat should be applied after the first coat has dried. It will dry with a nice luster, usually within 30 minutes.

## United 69

# All Surface Acrylic Sealer

**KEEP OUT OF REACH OF CHILDREN.**

## CAUTION

**SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.**

#### PRECAUCION AL USARIO:

*Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.*

**Manufactured and Sold Exclusively By:  
UNITED LABORATORIES, INC.**

**320 37th Avenue • St. Charles, IL 60174  
1-800-323-2594 • www.unitedlabsinc.com**

To remove the surface dirt, a mild detergent such as United 60 NEUTRA-CLEAN is all that is necessary. When the finish on the floor has become excessively dirty and worn, and it is desired to remove the finish, apply a concentrated detergent solution such as United 61 WAX STRIPPER to remove it. One part United 61 to 10 parts of hot water will easily remove the finish. After it has been removed, rinsed and dried, a new coat should be applied. In applying, do not rub in but apply with light, even strokes. No special skill is required to put on this seal.

Never pour the residue left in the applying pan or bucket back into the original container, as this may contaminate the unused material. **STORE CONTAINERS IN AREA PROTECTED FROM FREEZING.** Keep containers tightly closed when not being used, to prevent evaporation.

**CAUTION:** Contains Diethylene Glycol Monoethyl Ether (CAS#111-90-0), and Tributyoxyethyl Phosphate (CAS# 78-51-3). **DO NOT TAKE INTERNALLY. DO NOT GET ON SKIN OR IN EYES.**

#### EMERGENCY AND FIRST AID PROCEDURES:

**EYES:** Flush with plenty of water for at least 15 minutes. Seek immediate medical attention.

**SKIN:** Wash with soap and water and remove any contaminated clothing. If irritation persists, seek medical attention.

**INHALATION:** Remove to fresh air. Apply CPR if necessary. If breathing is difficult, give oxygen. Seek immediate medical attention.

**INGESTION:** Seek immediate medical attention. **DO NOT** induce vomiting. If conscious, dilute by drinking water. Never give anything by mouth to an unconscious person.

An MSDS for this product is available through United's website, [www.unitedlabsinc.com](http://www.unitedlabsinc.com), for 24-hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

<b>HMIS® III CODE:</b> 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE <b>PERSONAL PROTECTION INDEX:</b> Gloves and Goggles	HEALTH	1
	FLAMMABILITY	0
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	n&p