

# UNITED

LABORATORIES

## CLINGS TO VERTICAL SURFACES

A fast, economical stripping agent for WOOD or METAL surfaces. Removes most finishes such as paint, enamel, varnish, shellac, epoxy coatings and lacquer. Easier and faster to use than conventional brush-on products.

### DIRECTIONS FOR USE:

Read Cautions and Directions for Use Carefully before using.

SHAKE VIGOROUSLY BEFORE EACH USE.

TEST SMALL, INCONSPICUOUS AREA BEFORE USING.

- Protect surrounding objects from overspray. **NOTE: Product will harm Plastics and Floor Tile.**
- Hold can upright about 8 inches from surface to be cleaned. POINT VALVE AWAY FROM FACE. Apply a medium to heavy coat on surface.
- Allow product to remain on surface until bubbling action begins to lift surface coating. Time required will vary depending upon type of coating.
- When coating has lifted and before product dries, remove with steel wool, wire brush or scraper.
- Re-application may be required.
- After stripping the item, wipe entire surface with damp cloth and allow to completely dry. Wipe again with clean, dry cloth. The item is now ready for refinishing.

**For food plant use:** Food contact surfaces are to be washed and rinsed with potable water before reuse. Remove all food from the area prior to use of the product.

**NOTE:** For metal surfaces, another acceptable method is to hose off the item with water. If this alternate method is used, dry off the metal item to minimize flash rusting.

**WARNING:** This product contains a chemical(s) known to the State of California to cause cancer.

### HMIS® CODE:

0=MINIMAL  
1=SLIGHT  
2=MODERATE  
3=SERIOUS  
4=SEVERE

HEALTH/SANTÉ	3
FLAMMABILITY/INFLAMMABLE	2
REACTIVITY/RÉACTIVITÉ	0
PERSONAL PROTECTION PROTECTION PERSONNELLE	B

### PERSONAL PROTECTION INDEX:

GOGGLES and GLOVES

### WARNING:

**CONTAINS (CAS#):** Methylene Chloride (75-09-2), Propane/n-Butane (68476-86-8), Methanol (67-56-1), Methylcellulose (9004-65-3), Petroleum Wax (64742-43-4).

## LIFT OFF! WOOD AND METAL FINISH REMOVER

UNITED 189

KEEP OUT OF REACH OF CHILDREN  
**CAUTION**  
VAPOR HARMFUL  
HARMFUL IF SWALLOWED  
CONTENTS UNDER PRESSURE  
SEE SIDE PANEL FOR ADDITIONAL  
PRECAUTIONARY STATEMENTS

### Also Removes:

Paint ■ Varnish ■ Lacquer

Spray On—Let Penetrate  
Scrape or Flush Off

NET WEIGHT: 18 oz. (510 g)

**PRECAUCION AL USARIO:** Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Sold By:

**UNITED LABORATORIES, INC.**

320 37th Avenue • St. Charles, IL 60174

1-800-323-2594 • www.unitedlabsinc.com

### UNITED 189 LIFT OFF!

WOOD AND METAL FINISH REMOVER  
UNITED LABORATORIES OF CANADA, INC.

214 DOLOMITE DRIVE • DOWNSVIEW, ONTARIO M3J 2N2  
An M.S.D.S. for this product has been provided. Please read it carefully and follow all instructions when using or handling this product.

Une fiche signalétique a été fournie pour ce produit. Prière de la lire soigneusement et d'en suivre toutes les instructions pendant l'usage et la manipulation de ce produit.



Contents are under pressure. It may explode if heated. Contents may cause irritation and burns to the eyes and skin. Harmful if inhaled. Harmful if swallowed. Contains a mutagenic solvent (Methyl Alcohol). Contains a carcinogenic solvent (Methylene Chloride). Chronic overexposure may cause serious damage to health.

**PRECAUTIONS:** Avoid contact with eyes and skin. Wear safety glasses and gloves when handling or using this product. Wash thoroughly after handling. Do not ingest. Provide adequate ventilation to keep vapor concentration below 25 ppm in air. Avoid prolonged breathing of vapors. Vapor may be especially harmful to those with heart conditions. Do not use this product near flames or sources of ignition.

Do not puncture or incinerate this container, even when empty. Do not store at temperatures over 49°C.

**FIRST AID MEASURES: EYES:** Flush with water for at least 15 minutes and call a physician immediately. **SKIN:** Wash with soap and water. If irritation persists, call a physician.

**IF INHALED:** Remove to fresh air. Apply artificial respiration if needed. If irritation persists, call a physician. **IF SWALLOWED:** Induce vomiting. Call a physician immediately.

Le contenu est sous pression. Il peut exploser s'il est chauffé. Le contenu peut causer de l'irritation ou des brûlures pour les yeux ou la peau. Nocif s'il est inhalé. Nocif en cas d'ingestion. Contient un solvant mutagène (Alcool méthylique). Contient un solvant carcinogène (Chlorure de méthylène). La surexposition chronique peut causer des dommages sérieux à la santé.

**PRECAUTIONS:** Éviter tout contact avec les yeux, la peau. Utiliser des lunettes protectrices et des gants pendant l'usage de ce produit. Bien se laver après la manipulation. N'ingérer pas. Pourvoir une ventilation adéquate. N'utiliser pas ce produit près des flammes ou près des sources d'ignition. Ne perforer et n'incinérer pas ce contenant, même lorsqu'il est vide. N'entreposer pas à des températures excédant 49°C.

**PROCÉDÉS DE PREMIERS SOINS: POUR LES YEUX:** Laver à grande eau pendant au moins 15 minutes et appeler un médecin immédiatement. **POUR LA PEAU:** Laver avec du savon et de l'eau. Si l'irritation persiste, appeler un médecin. **EN CAS D'INHALATION:** Emmener au grand air. Administrer la respiration artificielle, au besoin. Si l'irritation persiste, appeler un médecin. **EN CAS D'INGESTION: PAS PROVOQUER LE VOMISSEMENT.** Appeler un médecin immédiatement.