

UNITED 205



MATERIAL SAFETY DATA SHEET

320 37th Avenue, St. Charles, Illinois 60174 • 214 Dolomite Drive, Downsview, Ontario M3J2N2
www.unitedlabsinc.com

To Reorder Call:
800-323-2594

1. PRODUCT AND COMPANY IDENTIFICATION

FOR MEDICAL AND TRANSPORTATION EMERGENCIES
24 Hour INFOTRAC (US and CANADA): 800-535-5053

PRODUCT NAME
UNITED 205 LAST STOP

USE/DESCRIPTION
Glue Traps

REVISION DATE
September 12, 2008

HEALTH (0 = Maximum Safety)

1

Always follow Label Directions and Cautions.

4 Extreme 3 High 2 Moderate 1 Slight 0 Minimal

See Hazards Identification Section of this MSDS for more detailed information.

FLAMMABILITY (0 = Maximum Safety)

1

Susceptibility of Material to Burning.

4 Extremely flammable. 1 Must be preheated
3 Ignites at normal temperature. to burn.
2 Ignites when moderately heated. 0 Will not burn.

REACTIVITY (0 = Maximum Safety)

0

Susceptible to Release of Energy.

4 May detonate-vacate area if materials are exposed to fire. 2 Violent chemical change possible-use hose stream from distance
3 Strong shock of heat may detonate-use monitors from behind explosion resistant barriers. 1 Unstable if heated-use precaution.
0 Normally stable.

PERSONAL PROTECTION:



2. COMPOSITION/INFORMATION ON INGREDIENTS

In accordance with Federal Regulation 29 CFR 1910.1200, all materials in this product are considered non-hazardous.

3. HAZARDS IDENTIFICATION

Eyes: May cause irritation.

Skin: May cause irritation.

Inhalation: For hot product, inhalation of vapors may cause irritation in the respiratory tract.

Ingestion: Small amounts are not expected to produce adverse health effects. Larger quantities (>1oz.) should be recovered from the stomach by aspiration.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes with water for at least 15 minutes while holding eyelids open. If irritation persists, call a physician or poison control center.

Skin: Wash affected area with soap and water. For hot product, immediately immerse in or flush the affected area with large amount of cold water to dissipate heat and reduce the extent of the thermal burns. Call a physician.

Inhalation: Move to fresh air. If irritation persists, call a physician or poison control center.

If Swallowed: Small amounts are not expected to produce adverse health effects. Larger quantities (>1oz.) should be recovered from the stomach. Aspiration of material into the lungs during vomiting may cause chemical Pneumonitis. Call a physician or poison control center immediately.

5. FIRE FIGHTING MEASURES

Flash Point (TCC): > 340° F/170°C (P.M.)

Explosive Limits: Lower (LEL): ND Upper (UEL): ND

Flame Projection (Aerosol): NA

Hazardous Products of Combustion: When strongly heated, as in fire, this product may produce CO₂, CO, and potentially irritating and toxic fumes.

Fire and Explosion Hazards: None known.

Extinguishing Media: Carbon dioxide, water spray

Fire Fighting Instructions: Firefighters should wear full protective equipment and NIOSH/MSHA approved self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Small Spills: Material is a solid adhesive and will not flow out. If recovery is not feasible, mix with dry soil, sand, or non-reactive absorbent and place in a container or dumpster. Wash area to remove remaining material.

Large Spills: Material is a solid adhesive and will not flow out. If recovery is not feasible, mix with dry soil, sand, or non-reactive absorbent and place in a container or dumpster. Wash area to remove remaining material. .

7. HANDLING AND STORAGE

Store in a cool, dry, and well ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Normally none required.

Skin: Rubber gloves are recommended.

Respiratory: Normally not required.

Engineering Controls: Normally not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: ND

Specific Gravity: 0.93

Vapor Pressure: ND

Melting Point: 325°F/163°C

Vapor Density: ND

Evaporation Rate: Negligible

Solubility in Water: Insoluble

pH: NA

Appearance and Odor: Clear to pale yellow tacky solid with petroleum odor.

10. STABILITY AND REACTIVITY

Hazardous Polymerization: Will not occur.

Hazardous Decomposition: When strongly heated, as in fire, this product may produce CO₂, CO, and potentially irritating and toxic fumes.

Chemical Stability: Stable

Incompatibility: Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity (NTP/IARC/OSHA): None

California Proposition 65: Does this product contain chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm? None

12. ECOLOGICAL INFORMATION

ND

13. DISPOSAL CONSIDERATIONS

Consult your local, state, provincial and federal regulations for proper disposal guidelines. Disposal regulations may be different for each state and/or locality.

14. TRANSPORT INFORMATION

DOT: Available upon request

TDG: Available upon request

UN: Availabale upon request

15. REGULATORY INFORMATION

VOC(Volatile Organic Compounds): None

TSCA (Toxic Substances Control Act): Listed

SARA Title III Section 302 EHS: None

SARA Title III Section 311/312: ND

SARA Title III Section 313 Toxic Chemicals: None

WHMIS Classification:

This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations/ WHMIS) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

Read and follow all label directions and precautions before using this product. These products are intended for industrial and institutional use only. NOT FOR HOUSEHOLD USE OR RESALE. KEEP OUT OF REACH OF CHILDREN.

UNITED 205 LAST STOP

PREPARED BY: Sandy Kopacz