
UNITED

LABORATORIES

DANGER: Contains Acetone (67-64-1), Polyalkylene glycol monobutyl ether (9038-95-3), Liquefied Petroleum Gas (68476-86-8), and Petroleum distillates, hydrotreated light (64742-47-8). Do not use near heat or open flame. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Avoid eye contact.

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention.

IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

Contains no ozone depleting chemicals.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product.

United 105

Cutting And Tapping Fluid

Drills • Taps • Cutting Tools

KEEP OUT OF REACH OF CHILDREN.

DANGER

EXTREMELY FLAMMABLE.

CONTENTS UNDER PRESSURE.

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

NET WT. 12 oz. (340 g)

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

UNITED LABORATORIES, INC.

**320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com**

HIGH POWERED FOR USE ON EXOTIC METALS

Stainless Steel, Chrome-Moly and Vanadium Steels, Carbon Steels, Inconel, Nitralloy Steel, Aluminum and Aluminum Alloys, Monel, Phosphor, Bronze, Hastelloy Alloys, Titanium, Beryllium Copper and other related alloys.

Synthetic lubricant effective in punching, sawing, machining, cutting, tapping, milling, grinding and threading operations on all steels and non-ferrous metals.

Increases production rates as well as tool life. Results in cooler workpiece with less tool burning. Fluid is transparent providing better visibility of work area.

DIRECTIONS:

1. Spray area to be worked generously.
2. Reapply as necessary to keep work area cool and well lubricated.
3. Can be removed with cold water or solvent degreaser.

HMIS® CODE 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX Consult Your Supervisor	HEALTH	1
	FLAMMABILITY	3
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	X

 Manufactured and Printed in U.S.A. 414