



UNITED

L A B O R A T O R I E S

United 922

HYDRASLIK Hydraulic Oil Anti-Wear, Thermally-Stable 10W-40

United 922 is a blend of highly refined base stocks plus the highest quality thermally stable additives.

These Additives Include:

- Anti-wear
- Anti-foam
- Anti-corrosive
- Anti-oxidation
- Water resistant: superior hydrolytic stability

Meets or exceeds these standards:

Sperry-Vickers	1-286-8, M-295-5
B.F. Goodrich	0152
Dennison	HF-0,1,2
Ford	M-6C32
U.S. Steel	136-127
G.M.	LH-04-1, LH-06-1, LH-15-1
Cincinnati Milacron	P68, 69, 70

CAUTIONS: DO NOT use in systems requiring water-based hydraulic oils.

KEEP OUT OF REACH OF CHILDREN.
CAUTION
CONTAINS PETROLEUM DISTILLATES.
HARMFUL OR FATAL IF SWALLOWED.
SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

PRECAUCION AL USUARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Sold By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

DIRECTIONS:

For best results drain all old oil and replace with **United 922**. Add **United 922** as needed between changes.

CAUTION:

Contains Petroleum Hydrocarbon Blend (CAS #'s 64742-58-1 and 64742-54-1). Harmful or fatal if swallowed. Avoid contact with skin and eyes.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: Flush with water for 15 minutes. If irritation persists, seek medical attention.

SKIN CONTACT: Wash with soap and water. If irritation occurs, seek medical attention.

INHALATION: Remove to fresh air. If breathing difficulties arise, seek medical attention.

IF SWALLOWED: Consult physician.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.