

UNITED

LABORATORIES

United 948

KOOL RED II

Extra Heavy Duty Grease

KEEP OUT OF REACH OF CHILDREN.

CAUTION
DO NOT TAKE INTERNALLY.
SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS.

NET WT. 14 oz. (397 g)

*PRECAUCION AL USARIO: Si usted no puede leer
Ingles, pregunte a alguien que le traduzca esta
etiqueta para usted antes de uso.*

Sold By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

United 948 KOOL RED II:

- Premium quality, lithium complex lubricating grease.
- Specially formulated to withstand high temperatures up to 400°F (204.4°C).
- Specially formulated to resist rust, oxidation, corrosion, salt spray, steam, dirt, dust and most acids.
- Protects against severe shock loading and pounding.
- Meets NLGI Certification GC-LB classification for use as wheel bearing and chassis lubrication.

DIRECTIONS:

It is recommended that all old grease be removed prior to using **United 948** to avoid potential incompatibility issues. Never mix greases of different soap base types.

TEST SPECIFICATIONS:

NLGI Grade:	2
Worked Penetration (ASTM D 217):	265-295 mm/10
Timken Load (ASTM D 2509):	60
Water Resistance:	Excellent
Oxidation Stability:	Excellent

CAUTION:

Do not ingest. If this should occur, drink large volumes of water and seek medical attention. Avoid storage of product in freezing temperatures. Keep container sealed when not in use.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with plenty of cool water for at least 15 minutes. If irritation occurs get medical attention.

SKIN: Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes before reuse. If irritation persists get medical attention.

INHALATION: Remove to fresh air immediately. For breathing difficulties oxygen may be necessary. Get medical attention if any discomfort continues.

INGESTION: DO NOT induce vomiting. If conscious, give several glasses of water to drink. Get medical attention.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMSI® III CODE 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX Glasses and Gloves	HEALTH	1
	FLAMMABILITY	1
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	B



Manufactured and Printed in U.S.A.

513