UNITED 949



MATERIAL SAFETY DATA SHEET

320 37th Avenue, St. Charles, Illinois 60174 • 214 Dolomite Drive, Downsview, Ontario M3J 2N2 www.unitedlabsinc.com

To Reorder Call: 800-323-2594


1. PRODUCT AND COMPANY IDENTIFICATION

UNITED 949 UNI-LUBE MP Multi-Purpose Grease

PRODUCT NAME

USE/DESCRIPTION Multi-Purpose Grease

FOR MEDICAL AND TRANSPORTATION EMERGENCIES 24 Hour INFOTRAC (US and CANADA): 800-535-5053 REVISION DATE April 28, 2010



2. COMPOSITION/INFORMATION ON INGREDIENTS

| | | | ACGIH | OSHA | ACGIH | LD50 |
|---|------|----------|-----------------------|-----------------------|------------------------|-----------------|
| Component | CAS# | %Range | (TLV-TWA) | (PEL-TWA) | (STEL) | (Species Route) |
| Lubricating oils, petroleum, base oils, highly refined ** | NE | 60 - 100 | 5 mg/m3 (oil mist) | 5 mg/m3 (oil mist) | 10 mg/m3 (oil mist) | NE |

**The petroleum base oils contained in this product have been highly refined by a variety of processes including solvent extraction, solvent dewaxing and hydrotreating to remove aromatics and improve performance characteristics.

3. HAZARDS IDENTIFICATION

Eyes: May be slightly irritating.

Skin: Prolonged or repeated contact may dry skin.

Inhalation: Not a likely route of exposure at room temperature. Heating can generate vapors that may cause headaches, nausea, and respiratory irritation.

Ingestion: May cause stomach pain or vomiting.

4. FIRST AID MEASURES

Eyes: Flush with plenty of cool water for at least 15 minutes. If irritation occurs get medical attention.

Skin: Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes before reuse. If irritation persists get medical attention.

Inhalation: Remove to fresh air immediately. For breathing difficulties oxygen may be necessary. Get medical attention if any discomfort continues.

Ingestion: DO NOT induce vomiting. If conscious, give several glasses of water to drink. Get medical attention.

5. FIRE FIGHTING MEASURES

 Flash Point (Cd OC):
 >450°F/>230°C (Cleveland Open Cup)
 Explosive Limits:
 Lower (LEL):
 ND
 Upper (UEL):
 ND

 Flame Projection (Aerosol):
 NA

Hazardous Products of Combustion: When strongly heated, as in a fire, this product may produce oxides of carbon, phosphorus, sulfur and acrid smoke/fumes.

Fire and Explosion Hazards: None known.

Extinguishing Media: Carbon dioxide, Dry chemical.

Fire Fighting Instructions: Wear self-contained positive breathing apparatus (SCBA) w/full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Small Spills: Soak up with an inert absorbent, such as clay or vermiculite and place in designated disposal container. Wash area thoroughly.

Large Spills: Minimize skin contact. Remove sources of ignition and ventilate area. Carefully collect spilled material enclosed containers. Soak up remaining with an inert absorbent, such as clay or vermiculite and place in designated closed disposal container. Wash area thoroughly. Do not let washing down water contaminated ponds or waterways.

7. HANDLING AND STORAGE

Store in a cool, dry area away from heat, sparks, and open flame. Keep containers closed. Avoid prolonged exposure to vapors and mists. Store separated from: Acids, Oxidizing materials. Avoid spilling, skin and eye contact. Eye wash and emergency shower must be available at the work place. Wash face and hands with soap and water after using this product. Launder contaminated clothing before reusing.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses are recommended.

Skin: Chemical resistant gloves required for prolonged or repeated contact. Use protective gloves made of: Neoprene, nitrile, polyethylene or PVC.

Respiratory: None required if good ventilation is maintained. Respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

Engineering Controls: Mechanical ventilation recommended when handling in enclosed/tight spaces.

Other protective Clothing: Wear appropriate clothing to prevent repeated or prolonged skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:NDSpecific Gravity:0.90 (H2O=1)Vapor Pressure:> 5Melting Point:NDVapor Density:< 0.1 mm Hg (air=1)</td>Evaporation Rate:< 0.1</td>Solubility in Water:InsolublepH:NAAppearance and Odor:Tan grease with oil odor.Tan grease with oil odor.NA

10. STABILITY AND REACTIVITY

 Hazardous Polymerization:
 Will not occur.

 Hazardous Decomposition:
 When strongly heated, as in a fire, this product may produce oxides of carbon, phosphorus, and sulfur.

 Chemical Stability:
 Stable

 Incompatibility:
 Avoid strong oxidizing agents and acids.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity (NTP/IARC/OSHA): None

California Proposition 65: Does this product contain chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm? None

12. ECOLOGICAL INFORMATION

ND

13. DISPOSAL CONSIDERATIONS

Consult your local, state, provincial and federal regulations for proper disposal guidelines. Disposal regulations may be different for each state and/or locality.

14. TRANSPORT INFORMATION

DOT: Available upon request **TDG:** Available upon request **UN:** Availabale upon request

15. REGULATORY INFORMATION

VOC(Volatile Organic Compounds): None TSCA (Toxic Substances Control Act): Listed SARA Title III Section 302 EHS: ND SARA Title III Section 311/312: ND SARA Title III Section 313 Toxic Chemicals: None WHMIS Classification: This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations/ WHMIS) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

Read and follow all label directions and precautions before using this product. These products are intended for industrial and institutional use only. NOT FOR HOUSEHOLD USE OR RESALE. KEEP OUT OF REACH OF CHILDREN.

UNITED 949 UNI-LUBE MP Multi-Purpose Grease

PREPARED BY: Sandy Kopacz