

UNITED

L A B O R A T O R I E S

UNITED 962 UNI-KOOL FS Full Synthetic Coolant is designed for use on all metals from cast iron to aluminum. While this product is formulated to provide the same lubricity properties as an oil containing coolant, there is no concern about fouling from bacterial and fungal growth commonly found with oil based coolants.

UNI-KOOL FS benefits include:

- High lubricity without oil.
- Drops cast iron fines readily.
- Excellent rust protection for machine and parts.
- Mixes easily in hard or soft water.
- Contains no chlorine or sulfur.
- Resists bacteria and fungus growth.
- Excellent operator acceptance.
- High lubricity for aluminum tapping.
- Will not stain non-ferrous metals.
- Rejects tramp oil for easy skimming.
- Very low foam.
- Cleaner than water soluble oils.

RECOMMENDED USE:

Recommended dilution for machining is between 3% and 5%.

Use of a 0 to 10 refractometer is suggested to manage coolant concentration. Refractometer factor of **UNITED 962** is 2.27.

UNI-KOOL FS Full Synthetic Coolant

UNITED 962

KEEP OUT OF REACH OF CHILDREN.

CAUTION

SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS.

PRECAUCION AL USARIO: Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Sold Exclusively By:

UNITED LABORATORIES, INC.

320 37th Avenue • St. Charles, IL 60174

1-800-323-2594 • www.unitedlabsinc.com

SPILL:

In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

HANDLING AND STORAGE:

Keep out of reach of children. Keep container tightly closed when not in use.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Immediately flush with plenty of water for at least 15 minutes. If irritation occurs get medical attention.

SKIN: Immediately flush with plenty of water for at least 15 minutes. Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes before reuse. If irritation persists get medical attention.

INHALATION: Remove to fresh air immediately. Get medical attention if symptoms appear.

INGESTION: DO NOT induce vomiting. If conscious, give several glasses of water to drink. Get medical attention.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS® III CODE:

0=MINIMAL
1=SLIGHT
2=MODERATE
3=SERIOUS
4=SEVERE

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

PERSONAL PROTECTION INDEX:

Glasses and Gloves