

# UNITED

LABORATORIES

Responsible Innovation™ - **SOLAR GOLD Lift Station Maintainer** harnesses the power of nature's resources to provide a bio-based blend that is uniquely suited for cleaning and deodorizing lift stations.

- NPE-Free.
- Non-caustic.
- Non-corrosive.
- Contains no petroleum distillates.
- Contains no chlorinated hydrocarbons.
- Deodorizes with a fresh citrus scent.

The excellent solvency of this product cuts grease and slime from the sidewalls of the station while the fresh citrus scent deodorizes even the most malodorous facilities.

## DIRECTIONS

Add sufficient material so that 1" (2.5 cm) or 2" (5.1 cm) of material floats on the surface of the water. This material will dissolve and solubilize grease accumulations in the lift station, as well as the grease accumulations on the side walls where it comes in contact.

Ask your United Representative for your suggested weekly maintenance dose. The recommended maintenance dose (1/4 of your initial dose per week) is strictly a suggested starting point. Conditions of use and load requirements may cause this to vary widely.

## IMPORTANT

Be sure float is solvent resistant and is set, so the water level never goes to the point where the station is completely pumped out. Enough water should always remain in the station, to keep this maintainer intact. Submersed pumps and wiring must be solvent resistant. **United 633** will attack plastics, rubber, neoprene and soft materials. **DO NOT USE SOLAR GOLD LIFT STATION MAINTAINER IN A TURBULENT LIFT STATION.**

When using a metering pump with this product, you must use Viton® tubing.

**SOLAR GOLD**

**633**

## Lift Station Maintainer

**KEEP OUT OF REACH OF CHILDREN.**

## CAUTION

**SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.**

### PRECAUCION AL USARIO:

*Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.*

**Manufactured and Sold Exclusively By:**  
**UNITED LABORATORIES, INC.**  
320 37th Avenue • St. Charles, IL 60174  
1-800-323-2594 • [www.unitedlabsinc.com](http://www.unitedlabsinc.com)

## CAUTION

Contains d-1,8 (9)-p-Menthadiene (CAS #5989-27-5). **United 633** is combustible and should be stored in a cool place away from exposure to extreme heat and open flames. It may ignite and burn on heating above 110°F (43°C). Product may catch fire in use.

Harmful if swallowed. Avoid eye and skin contact.

## EMERGENCY AND FIRST AID PROCEDURES

**EYES:** Flush with plenty of tepid water for at least 15 minutes while holding eyelids open. Call a physician or poison control center immediately.

**SKIN:** Wash with soap and water. If irritation persists, call a physician or poison control center.

**INHALATION:** Remove to fresh air. Apply CPR if needed. Call a physician or poison control center immediately.

**INGESTION:** DO NOT induce vomiting. Call a physician or poison control center immediately.

An MSDS for this product is available through United's website, [www.unitedlabsinc.com](http://www.unitedlabsinc.com), providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

|   |                     |   |
|---|---------------------|---|
| <b>HMIS® III CODE:</b><br>0=MINIMAL 1=SLIGHT<br>2=MODERATE<br>3=SERIOUS 4=SEVERE<br><b>PERSONAL PROTECTION INDEX:</b><br>Gloves and Goggles | HEALTH              | 1 |
|   | FLAMMABILITY        | 2 |
|   | PHYSICAL HAZARD     | 0 |
|   | PERSONAL PROTECTION | B |