





LABORATORIES

OIL EATER Hydrocarbon Eliminator Block with Inter-Core Technology is an innovative, easy-to-use biological solution specifically selected and adapted to degrade diesel, gasoline, motor oil and other organic compounds found in municipal collection systems. OIL EATER is an extremely effective, low-maintenance means of controlling hydrocarbon-based pollutants found in storm water runoff.

The innovative Inter-Core Technology combines the staying power of proven block technology with the instant concentrated dosage of a granular active.

- The core of the **OIL EATER** consists of 10 billion CFU/g count of a special bacterial blend that is released as a slug dose into the waste stream within minutes.
- The **OIL EATER** block is a special blend of bacteria. The 10 billion CFU/g block is designed to release its bacteria over an extended time (60-180 days).
- Earth Smart® Certified.
- Degrades most hydrocarbons.
- Easy-to-use block requires minimal attention.
- Eliminates need for harsh, corrosive chemicals.
- Safe for all types of lines will not corrode the system.
- Contains facultative anaerobes which degrade with or without oxygen.
- Reduces the amount of Oil and Grease blockages, does not just move it further downstream.

DIRECTIONS FOR USE:

Every system must be treated according to its specific organic mix and operational parameters. Variances may be necessary.

Sumps: OIL EATER block should be suspended in the sump so the block is just under the surface. Apply one 2 lb. block for every 350 gallons capacity. If capacity is over 350 gallons, spread the blocks out in different sections of the sump.

Manholes and Mains: In manhole, OIL EATER block should be placed in the U channel nearly vertically on the upstream end of the U channel.

United 985

OIL EATER

Hydrocarbon Eliminator Block

with Inter-Core Technology
Patent Pending

KEEP OUT OF REACH OF CHILDREN. CAUTION

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

DIRECTIONS FOR USE: (continued)

Lift Stations: OIL EATER block should be used in low flow applications. Suspend the block so the entire block is submerged below the water at its lowest level.

Lift Station Flow	Block Size	Recommended number of OIL EATER Hydrocarbon Eliminator Blocks
Under 50,000 GPD	2 lb.	1
50,000 – 100,000 GPD	2 lb.	2
> 100,000 GPD	2 lb.	Please contact your United Representative

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush eyes with cool water for at least 15 minutes while keeping eyelids open. If irritation persists, seek medical attention.

SKIN: Wash with soap and water. Launder clothing. If irritation or redness persists, seek medical attention.

INHALATION: Not applicable.

IF SWALLOWED: Thoroughly rinse mouth with water. Drink one or two glasses of water. Slight gastrointestinal discomfort may occur.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product.

HMIS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Glasses and Gloves	HEALTH	0
	FLAMMABILITY	0
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	В