

# UNITED

LABORATORIES

Use on equipment throughout the year to provide a slick, non-stick coating that provides superior release action. **UNITED 127** protects metal, fiberglass, painted and plastic finishes. Applying **SEASONAL EQUIPMENT WAX** to these types of surfaces reduces drag and sticking of many materials to the surface. It also leaves surfaces water and rust resistant.

#### In Spring, Summer and Fall:

Treat lawn mower decks, blades, weed wackers, chippers, edgers and trimmers to lessen drag and increase efficiency. **SEASONAL EQUIPMENT WAX** will keep damp grass and other clippings from sticking to treated surfaces, while protecting metal surfaces from the corrosive effects of fertilizer and other lawn care treatments.

#### In Winter:

Use **UNITED 127** to treat snow plows, shovels, street signs and road signs to prevent ice and snow from sticking to their surfaces. **SEASONAL EQUIPMENT WAX** increases plow efficiency and helps protect metal surfaces from the corrosive effects of the winter weather, salt and other treatments that are used to keep roadways, parking lots and walkways clear of snow and ice.

#### Directions:

**Shake well before using.** Spray surface (comes out as a fine mist) from about 12 – 14 inches away. Allow a moment for wax coating to set up, but before the surface dries buff it with a clean cloth. After use, invert the can and spray a short burst to clear valve.

Manufactured & Printed in U.S.A.

1108

## SEASONAL EQUIPMENT WAX

UNITED 127

KEEP OUT OF REACH OF CHILDREN.

**DANGER**

EXTREMELY FLAMMABLE.

VAPOR HARMFUL.

CONTENTS UNDER PRESSURE.

SEE SIDE PANEL FOR ADDITIONAL

PRECAUTIONARY STATEMENTS.

*PRECAUCION AL USUARIO: Si usted no puede leer Ingles,  
pregunte a alguien que le traduzca esta etiqueta  
para usted antes de uso.*

**NET WEIGHT: 11 OZ. (311 grams)**

Sold By:

**UNITED LABORATORIES, INC.**

320 37th Avenue • St. Charles, IL 60174

1-800-323-2594 • [www.unitedlabsinc.com](http://www.unitedlabsinc.com)

**Contains No Chlorinated Solvents and No CFC's**

**DANGER:** Contains Hexane (CAS# 110-54-3), Liquefied Petroleum Gas (CAS# 68476-86-8) and Aliphatic Petroleum Distillates (CAS# 64742-89-8). Use only in a well ventilated area. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat, sparks or open flame. Do not store at temperatures above 120°F (49°C).

#### FIRST AID MEASURES:

**EYES:** Flush with large amounts of cool running water for 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

**SKIN:** Wash with soap and plenty of water. If irritation persists seek medical attention.

**INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops, give artificial respiration.

**INGESTION:** DO NOT induce vomiting. Seek medical attention immediately.

Highly concentrated and not intended for consumer household use.

An MSDS for this product has been provided. Please read it carefully and follow all instructions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

#### HMIS® CODE:

0=MINIMAL  
1=SLIGHT  
2=MODERATE  
3=SERIOUS  
4=SEVERE

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	B

#### PERSONAL PROTECTION INDEX:

GLASSES and GLOVES