



MATERIAL SAFETY DATA SHEET

320 37th Avenue, St. Charles, Illinois 60174
www.unitedlabsinc.com - www.uitedlabsinc.ca

To Reorder Call:
 800-323-2594

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME
 UNITED 626 WIPE OFF

USE/DESCRIPTION
 Graffiti Packs

FOR MEDICAL AND TRANSPORTATION EMERGENCIES
 24 Hour INFOTRAC (US and CANADA): 800-535-5053

REVISION DATE
 March 20, 2014

HMIS III HEALTH (0 = Maximum Safety) 2

Always follow Label Directions and Cautions.

* Chronic 2 Moderate
 4 Severe 1 Slight
 3 Serious 0 Minimal
See Hazards Identification Section of this MSDS for more detailed information.

PHYSICAL HAZARD (0 = Maximum Safety) 0

Susceptible to Release of Energy.

4 May detonate-vacate area if materials are exposed to fire. 2 Violent chemical change possible-use hose stream from distance
 3 Strong shock of heat may detonate-use monitors from behind explosion resistant barriers. 1 Unstable if heated-use precaution.
0 Normally stable.

FLAMMABILITY (0 = Maximum Safety) 3

Susceptibility of Material to Burning.

4 Extremely flammable. 1 Must be preheated
 3 Ignites at normal temperature. to burn.
 2 Ignites when moderately heated. 0 Will not burn.

PERSONAL PROTECTION: B



2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS#	%Range	ACGIH (TLV-TWA)	OSHA (PEL-TWA)	ACGIH (STEL)	LD50 (Species/Route)
Tripropylene glycol monomethyl ether	25498-49-1	10 – 30	NE	NE	NE	NE
Acetone	67-64-1	5-10	500 ppm	1000 ppm	750 ppm	5800 mg/kg rat
Methoxyisopropanol	107-98-2	7-13	100 ppm	100 ppm	150 ppm	NE
2-Butoxyethanol (skin designation)	111-76-2	5-10	20 ppm	50 ppm	NE	470 mg/kg rat
Amyl Acetate	628-63-7	1-5	50 ppm	100 ppm	100 ppm	1600ml/kg rat

3. HAZARDS IDENTIFICATION

Eyes: Causes irritation, redness, tearing or burning in eyes. May cause serious eye irritation.
Skin: May cause irritation, harmful if absorbed through intact skin. Repeat or prolonged occupational exposure can cause dermatitis, severe skin irritation, or Painter's Syndrome.
Inhalation: May be harmful. Overexposure to vapors may induce central nervous system effects. Excessive inhalation may cause irritation to nose, throat, lungs and upper respiratory tract.
Ingestion: Not an expected route of exposure. May be harmful or fatal. Aspiration hazard. May cause stomach upset, nausea, drowsiness, dizziness, headaches fatigue, and loss of coordination.

4. FIRST AID MEASURES

Eyes: Immediately flush with cool water. Remove contact lenses, if applicable, and continue flushing for 15 minutes. Obtain medical attention immediately.
Skin: Immediately flush with cool water for 15 minutes while removing contaminated clothing and shoes. Discard or wash well before reused. Obtain medical attention if irritation persists.
Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. If breathing has stopped, trained personnel should administer CPR immediately.
Ingestion: DO NOT induce vomiting. Rinse mouth with water, then drink one or two glasses of water. Obtain medical attention. Never give anything by mouth if victim is unconscious.

5. FIRE FIGHTING MEASURES

Flash Point (PMCC): 62°F/16.7°C **Explosive Limits:** Lower (LEL): ND Upper (UEL): ND

Flame Projection (Aerosol): N/A

Hazardous Products of Combustion: Carbon dioxide, carbon monoxide, smoke, soot and various organic oxidation by-products.

Fire and Explosion Hazards: Flammable liquid on a polypropylene towel. Large spills may cause a floating fire to form as in an oil fire.

Extinguishing Media: Carbon dioxide, dry chemical, foam, or water fog.

Fire Fighting Instructions: Wear self-contained breathing apparatus w/full protective clothing. Keep containers cool and vapors down with water spray. Prevent runoff from entering sewers and public waterways.

6. ACCIDENTAL RELEASE MEASURES

Small Spills: Wipe up small releases with a dry absorbent cloth or other absorbent material.

Large Spills: Not likely as liquid is absorbed on a towel. If a large amount of liquid is released absorb liquid with vermiculite, absorbent cloth, or other absorbent material. Prevent material from entering sewers or drains. Ventilate area. Transfer contaminated material into suitable container for proper disposal.

7. HANDLING AND STORAGE

Store in a cool, dry place away from heat sources. Keep container tightly sealed when not in use. Use with adequate ventilation. Keep out of reach of children. Do not inhale vapors. Follow label directions carefully. Do not get into eyes, on skin, or clothing. Wash thoroughly after handling. Do not swallow. Do not smoke while using.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Chemical safety glasses with side shields or goggles are recommended.

Skin: Impervious gloves are recommended if direct contact is possible.

Respiratory: Not usually required. Use with adequate ventilation. If TLVs are exceeded use a NIOSH/MSHA approved respirator.

Engineering Controls: Provide adequate ventilation. Local exhaust is generally adequate. Ventilation should be provided in the event of overexposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 212°F/100°C **Specific Gravity:** 0.986 (79°F) **Vapor Pressure:** ND **Melting Point:** ND

Vapor Density: >1 **Evaporation Rate:** ND **Solubility in Water:** Miscible **pH:** 6-6.5

Appearance and Odor: Clear colorless liquid with a banana scent on a towel.

10. STABILITY AND REACTIVITY

Hazardous Polymerization: Will not occur.

Hazardous Decomposition: Carbon dioxide, carbon monoxide, smoke, soot and various organic oxidation by-products.

Chemical Stability: Stable

Incompatibility: Keep away from strong alkalis, acids, oxidizers, alkali metal hydroxides and heat.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol	A3	Group 3		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3: Not Classifiable as to its Carcinogenicity to Humans

California Proposition 65: Does this product contain chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm? None

12. ECOLOGICAL INFORMATION

ND

13. DISPOSAL CONSIDERATIONS

Consult your local, state and federal regulations for proper disposal guidelines. Disposal regulations may be different for each state and/or locality.

14. TRANSPORT INFORMATION

DOT-Land USA: Consumer commodity, ORM-D

TDG: Available upon request

UN: Available upon request

15. REGULATORY INFORMATION

VOC (Volatile Organic Compounds): 295.80 grams per liter or 30% by weight

TSCA (Toxic Substances Control Act): Listed

SARA Title III Section 302 EHS: Acetone (CAS# 67-64-1) – 5000 lbs

SARA Title III Section 311/312: Acute Health Hazard - Yes; Fire Hazard - Yes; Chronic Health Hazard - No; Sudden Release of Pressur Hazard - No; Physical Hazard - No

SARA Title III Section 313 Toxic Chemicals: 2-Butoxyethanol (CAS# 111-76-2) – 5-10%; Tripropylene glycol monomethyl ether (CAS# 25498-49-1) 10-30%

WHMIS Classification:

This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations/ WHMIS) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

Read and follow all label directions and precautions before using this product. These products are intended for industrial and institutional use only. NOT FOR HOUSEHOLD USE OR RESALE. KEEP OUT OF REACH OF CHILDREN.