

UNITED

LABORATORIES

A heavy duty, non-chlorinated formula that removes brake fluid, grease, oil, dust and operating erosion from brake parts, pads, discs, linings and drums. Dries fast, residue free. Safe on most automobile plastic surfaces.

USE ON:

Brake Linings, Cylinders, Drums, Springs, Clutches, C.V. Joints, Disc Brake Calipers and other Related Brake Parts.

DIRECTIONS:

Protect all rubber brake parts and painted surfaces from product and overspray. DO NOT spray directly on painted surfaces. DO NOT apply while equipment is energized. Wet down surfaces to be cleaned using short bursts from a distance of 18-24 inches. Avoid breathing any dust or vapors that may become airborne. After all surfaces have been wetted, continue spraying to remove contaminants. Air dry or wipe with a clean cloth. For heavy deposits, repeat application as necessary. Runoff should be collected and disposed of properly.

IMPORTANT: If spilled or sprayed on painted surface, wipe off or wash off immediately.

DANGER:

 **POISON.** Contains Acetone (67-64-1), Toluene (108-88-3), Methanol (67-56-1) and Carbon Dioxide (124-38-9). Cannot be made non-poisonous. Do not puncture, incinerate or store can at temperatures above 120° F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Keep away from flames and other ignition sources. Over exposure to vapors can cause eye and skin irritation, headaches, nausea, dizziness, irritation to upper respiratory tract and irregular heartbeats. High concentrations have caused liver and kidney effects in laboratory animals. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use only in well-ventilated areas. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Vapors are heavier than air and can collect in low areas. If ventilation is not adequate, respiratory protection should be used.

United 111

Brake Parts Cleaner



*For fast removal of
grease, oil, fluid, and
asbestos particles.*

KEEP OUT OF REACH OF CHILDREN.

DANGER

EXTREMELY FLAMMABLE

VAPOR HARMFUL

 **POISON. MAY BE FATAL OR
CAUSE BLINDNESS IF SWALLOWED**

CONTENTS UNDER PRESSURE

SEE OTHER CAUTIONS ON BACK PANEL

NET WT. 16 OZ. (1 LB.) (453 GRAMS)

PRECAUCION AL USARIO: Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Sold By:
UNITED LABORATORIES, INC.

320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

- Blasts Away Deposits
- No Chlorinated or Fluorinated Solvents
- No Fouled Waste Oil
- Removes Brake Fluid, Grease and Oil
- Reduces Soil Wear on Parts
- Contains No Lead, Phosphorous or Silicone

FIRST AID

IF EYE CONTACT: Flush with large amounts of cool running water for 15 minutes, while holding upper and lower lids open. If irritation persists get medical attention immediately.

IF SKIN CONTACT: Remove contaminated clothing. Wash affected area with soap and water. If irritation persists, seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

SPECIAL USAGE WARNINGS: Contents Extremely Flammable. Do not smoke while spraying. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily in condensed spaces such as garages, engine compartments and low-lying areas. Static electricity may ignite vapors. Use only with adequate ventilation. Circulate fresh air during use and until vapors are gone.

KEEP OUT OF REACH OF CHILDREN

For further information consult Material Safety Data Sheet.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

HMS III® CODE 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX Glasses and Gloves	HEALTH	2
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	B