
UNITED

LABORATORIES

**FOR INDUSTRIAL AND
INSTITUTIONAL USE ONLY.**

- 100% Silicone Rubber.
- Retains flexibility indefinitely... won't crack or shrink.
- Bonds and fastens metal, rubber, plastic, tile, wood, porcelain, glass, ceramics, etc.
- Insulates and waterproofs.
- No caulk gun needed.
- Use only as much as you need.
- Controlled bead allows you to put the material exactly where you want it.
- Extension nozzle included for hard-to-reach places.
- Cured product works at temperatures from -60°F. to 450°F.

DIRECTIONS:

1. Clean and dry surface. Remove oil, grease or soap from surface.
2. Cut nozzle at desire bead size and apply bead of silicone. (Leave small bead of material which will form a sealing 'plug' for reuse. For reuse, gently pull 'plug' and begin to use material. If plug breaks leaving the dispensing tip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.)
3. Sealant normally "skins over" in 5 minutes and dries tack free to the touch in one hour. If spreading or working material is required do immediately after applying. Paper towels can be used to remove excess.
4. Sealant cures and bonds fully in 24 hours and maximum strength is achieved in 7 days.
5. For food use, sealant must be washed thoroughly before use. Sealant is easily trimmed with a sharp tool. Do not destroy bond by undercutting.

PERMA-FLEX Sealant and Adhesive Black, Clear, Red, White

UNITED 198

KEEP OUT OF REACH OF CHILDREN.

CAUTION

CONTACT WITH UNCURED SEALANT
CAUSES IRRITATION. CONTENTS UNDER
PRESSURE. OUTER CONTAINER IS
PRESSURIZED WITH A FLAMMABLE
HYDROCARBON PROPELLANT. DO NOT
REMOVE RUBBER PLUG. Read rear panel
for other cautions.

*PRECAUCION AL USARIO: Si usted no puede
leer Ingles, pregunte a alguien que le traduzca
esta etiqueta para usted antes de uso.*

*This product meets the requirement of FDA
Regulation No. 21CFR 177.2600, when fully
cured and washed. This formulation has been
certified to Federal Specification TT-S-001543A
Class A (COM-NBS), TT-S-00230 Class A
(COM-NBS) for silicone building sealants and
MIL-A-46106A.*

NET WT: 8 OZ. (226 g)

UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

MULTIPLE USES:

SEALING	CAULKING
Windows	Joints
Parts	Duct Work
Showers & Tubs	Wood Work
Pipe Joints	Equipment Housings

BONDING	GASKETING
Gaskets	Oil Pans
Appliance Parts	Water Pumps
Sign Letters	Valve Covers
	Compressors
	Hose Connections

FIRST AID:

EYES: Flush with water for at least 15 minutes and call a physician or poison center immediately.

SKIN: Remove completely with a dry cloth or paper towel before washing with detergent and water. If irritation persists, call a physician or poison center.

INHALATION: Remove to fresh air. If irritation persists, call a physician or poison center.

IF SWALLOWED: Call a physician or poison center immediately.

CAUTION:

Contains Methyltriacetoxysilane (CAS # 4253-34-3), Silica, Amorphous (CAS # 7631-86-9), Ethyltriacetoxysilane (CAS # 17689-77-9).

Do not puncture or incinerate. Do not store at temperatures above 120°F. Do not store in automobiles, in direct sunlight, or any area with temperatures above 120°F. Use with adequate ventilation. Product releases a vinegar like odor during application and use.

An MSDS for this product has been provided. Please read it carefully and follow all instructions when using or handling this product.

Printed in U.S.A.

1105