

UNITED

LABORATORIES



United 423

WHITE GUARD

White Food-Grade Grease

KEEP OUT OF REACH OF CHILDREN.

CAUTION
SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS.

NET WT. 14 oz. (397 g)

*PRECAUCION AL USARIO: Si usted no puede leer
Ingles, pregunte a alguien que le traduzca esta
etiqueta para usted antes de uso.*

Sold By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

- H1 USDA Rating.
- Premium quality-high performance grease.
- Excellent performance under a wide variety of operating conditions.
- Protects against severe shock loading and pounding.
- Compounded with anti-splatter and anti-wear additives.
- Inhibits rust and oxidation.
- Highly resistant to water washout.
- Ultra low odor.
- Non-staining, won't discolor or oxidize.

Recommended for use in Meat Packing Plants, Poultry Plants, Fish Packing Plants, Bottling Companies, and Restaurants operating under USDA guide lines.

DIRECTIONS FOR USE:

Remove old grease before applying this product. Never mix greases of different soap base types.

TYPICAL SPECIFICATIONS

NLGI Grade	2
Soap Type	Aluminum Complex
Texture	Smooth
Color	White
Worked Penetration, D-217, 77°F, 60 strokes	265-295
Dropping Point, D-2265, °F min.	500-550
Rust & Corrosion, D-1743	Pass
Timken, D-2509, Ok load, min.	40-50lbs
Four Ball EP, D-2596, Weld Pt. Kg min.	200-315 Kg
Copper Corrosion, D4048	1b
Flash Point, °F (°C)	455 (235)

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with plenty of cool water for at least 15 minutes. If irritation occurs get medical attention.

SKIN: Wash with soap and water.

INHALATION: Remove to fresh air immediately. For breathing difficulties oxygen may be necessary. Get medical attention if any discomfort continues.

INGESTION: DO NOT induce vomiting. Get medical attention.

Notes to Physician: High pressure injection under the skin may have serious consequences and may require urgent treatment.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS® III CODE 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX Glasses and Gloves	HEALTH	1
	FLAMMABILITY	1
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	B



Manufactured and Printed in U.S.A.

213